

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WATER-BASED PUTTY - ALL COLORS

PRODUCT NAME: FAMOWOOD WATER-BASED PUTTY - ALL COLORS
PRODUCT CODE: MSDS FAMO H2O PUTT

HMIS CODES: H F R P
1 0 0 B

===== SECTION 1 - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ECLECTIC PRODUCTS, INC.
ADDRESS : 1075 ARROWSMITH
EUGENE OR 97402

EMERGENCY PHONE : (800) 535-5053
INFORMATION PHONE : (800) 767-4667
DATE REVISED : 1/15/02
DATE PRINTED : 09/26/02
NAME OF PREPARER : Regulatory Compliance

===== SECTION 2 - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
-----------------------	------------	--------------------------------	-------------------

Wood Dust

ACGIH TLV: TWA=1 mg/m3 (hardwood), 5 mg/m3 (softwood)
ACGIH TLV: STEL=10 mg/m3 (softwood)
OSHA PEL: TWA=15 mg/m3 (nuisance dust), 5 mg/m3 (respirable fraction)

Crystalline Silica 14808-60-7

OSHA PEL: TWA=10mg/m3 respirable dust, 30mg/m3 total dust
ACGIH TLV: TWA=0.1 mg/m3 respirable dust
Limestone and natural iron oxide used in making this product contain silica as an impurity. Prolonged exposure to respirable crystalline dust may increase the risk of developing a disabling lung disease called silicosis. The International Agency for Research on Cancer (IARC) believes there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica from occupational sources.

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. *** # Proposition 65 Statement: This product contains a chemical known to the State of California to cause cancer.

DOT Classification: Not Regulated

===== SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 212 F. (100 C.) SPECIFIC GRAVITY (H2O=1): 1.70
VAPOR DENSITY: Heavier than air. MATERIAL VOC: 0.08 lb/gl
EVAPORATION RATE: Slower than ether. SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Colored putty with mild odor.

VOC calculations are based on the federal EPA definition of volatile organic compound under the Clean Air Act. State and local air quality authorities may have more stringent regulation.

===== SECTION 4 - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WATER-BASED PUTTY - ALL COLORS

Page: 2

EXTINGUISHING MEDIA: CO2, Dry Chemical, Water Fog

SPECIAL FIREFIGHTING PROCEDURES

None. Water may be used to cool fire exposed containers to keep from rupturing.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None.

===== SECTION 5 - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID

None.

INCOMPATIBILITY (MATERIALS TO AVOID)

None.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May form carbon dioxide, carbon monoxide, and various hydrocarbons upon combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION 6 - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

None.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause irritation to eyes and skin upon contact.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

None.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

None known. However, ingestion of product may cause gastrointestinal irritation.

HEALTH HAZARDS (ACUTE AND CHRONIC)

None.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No

Prolonged and repeated inhalation of wood dust or respirable crystalline silica containing dust in excess of appropriate exposure limits may cause silicosis, a lung disease. (*Please note Section II/Hazardous Ingredients to determine if wood dust or crystalline silica are present.*)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

None known.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with plenty of clean water for 15 minutes while lifting eyelids. If irritation persists, seek medical aid. **SKIN:** Wash thoroughly with soap and water. If irritation develops, seek medical attention. **INGESTION:** If swallowed, get medical attention.

M A T E R I A L S A F E T Y D A T A S H E E T

FAMOWOOD WATER-BASED PUTTY - ALL COLORS

Page: 3

===== SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Shovel in container and wash area with detergent and water. This product contains less than 1% of a component which is toxic to fish.

WASTE DISPOSAL METHOD

If material is dry, dispose of in landfill approved for industrial solid waste. If material is wet, dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in cool, dry, well ventilated area between 40 F. (4 C.) and 90 F. (32 C.). Keep from freezing as product stability will be affected.

OTHER PRECAUTIONS

None.

===== SECTION 8 - CONTROL MEASURES =====

RESPIRATORY PROTECTION

A dust respirator is recommended when sanding cured putty. Work station conditions should be evaluated by management to determine proper protective equipment.

VENTILATION

None required.

PROTECTIVE GLOVES

May be used if skin is sensitive.

EYE PROTECTION

Splashing is unlikely. However, safety glasses are suggested in accordance with good industrial hygienic practices.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

None (unless needed to protect regular clothing).

WORK/HYGIENIC PRACTICES

Wash thoroughly after use.

===== SECTION 9 - DISCLAIMER =====

To the best of our knowledge, the information provided herein is accurate, obtained from sources believed to be accurate. Since the conditions and methods of use of our product are beyond our control, we disclaim any and all liability arising out of the improper use of this product or the information provided herewith.